

# Convex relaxation techniques for set-membership identification of LPV systems

V. Cerone, D. Piga, D. Regruto

**Abstract**—Set-membership identification of single-input single-output linear parameter varying models is considered in the paper under the assumption that both the output and the scheduling parameter measurements are affected by bounded noise. First, we show that the problem of computing the parameter uncertainty intervals requires the solutions to a number of nonconvex optimization problems. Then, on the basis of the analysis of the regressor structure, we present some *ad hoc* convex relaxation schemes to compute parameter bounds by means of semidefinite optimization. Advantages of the new techniques with respect to previously published results are discussed both theoretically and by means of simulations.

**Index Terms**—Bounded error identification, Linear Parameter Varying, LMI relaxation, Parameters bounds.

## I. INTRODUCTION

Linear parameter varying (LPV) models belong to the more general class of linear time-varying models and, roughly speaking, they can be defined as linear systems where either the matrices of the state equations or the coefficients of the difference equation relating the input and the output signals depend on one or more time varying parameters whose real-time measurements are assumed to be available. These models have received a considerable attention from the identification and control community in recent years and can now be considered as one of the most popular tool to derive mathematical description of nonlinear/time-varying phenomena. As to the identification of LPV models, a relevant number of approaches has appeared in the literature since the work by Nemani, Ravikanth and Bamieh [1] which seems to be the first paper addressing the problem. They consider linear parameter varying models with a single time-varying parameter and assume that the measurements of all the state variables are available. A parameter estimation scheme based on the minimization of a prediction error cost function is proposed in [2] where LPV models with multiple time-varying parameters are considered under the assumption of LFT parameter dependence. Least mean square and recursive least square algorithms are proposed in [3] to solve the identification of LPV input-output models assuming that measurements of input, output and scheduling parameters are available. Persistency of excitation conditions in terms of inputs and scheduling parameters trajectories are also derived. Subspace identification of multiple input multiple output (MIMO) LPV models with affine parameters

dependence is considered in a number of papers. In [4] it is shown that standard subspace algorithms cannot be used in practice to identify LPV models since the dimensions of the data matrices grow exponentially with the system order. Significant improvements over the method proposed in [4] are presented in [5], exploiting kernel methods, and in [6] where an instrumental variable approach is considered and the positive effect of using periodic scheduling sequences is highlighted. Iterative subspace system identification is considered in [7]. Application of LPV subspace identification algorithms to both periodic and nonlinear systems are discussed in [8] where the proposed approach is applied to the modeling of helicopter rotor dynamics. Separable least squares are exploited in [9] to derive a novel algorithm for a class of nonlinear parameter-varying models represented in the form of a linear fractional transformation, while an orthonormal basis functions based approach is presented in [10]. A detailed overview of the available LPV modeling and identification approaches can be found in the recent book [11] by Toth, where the nontrivial relation between state-space and input-output description for LPV systems is also discussed. In all the papers mentioned above, the measurement error is statistically described. An alternative to the stochastic description of measurement errors is the bounded-errors or set-membership characterization, where uncertainties are assumed to belong to a given set (see, e.g., [12]). In this context, all parameters belonging to the *feasible parameter set (FPS)*, i.e. parameters consistent with measurements, error bounds and the assumed model structure, are feasible solutions to the identification problem. To the authors best knowledge, only a couple of contributions address the identification of LPV models when measurement errors are supposed to be bounded. In [13] the problem of identification and model validation of LPV systems in the presence of bounded noise and a possible nonparametric part is considered. A solution is proposed recasting the problem in terms of checking the feasibility of a set of linear matrix inequalities. In [14] the author consider the identification of discrete-time LPV models with finite impulse response structure and output measurements affected by bounded noise.

In this paper a procedure for set-membership identification of SISO discrete-time LPV models when both the output and the time-varying parameters measurements are affected by bounded noise is considered. Preliminary results on this problem are presented in [15] and successfully applied to the problem of deriving an LPV model of the vehicle

The authors are with the Dipartimento di Automatica e Informatica, Politecnico di Torino, corso Duca degli Abruzzi 24, 10129 Torino, Italy; e-mail: vito.cerone@polito.it, dario.piga@polito.it, diego.regruto@polito.it; Tel: +39-011-564 7064; Fax: +39-011-564 7198

lateral dynamics in [16]. Thanks to a careful analysis of the problem structure, a new convex relaxation approach is proposed in this paper to compute the parameter uncertainty intervals by means of semidefinite optimization. The obtained bounds are proven to be tighter than those obtained in [15]. The paper is organized as follows. Section II is devoted to the problem formulation. In Section III we show that computation of tight parameters bounds requires the solution to nonconvex optimization problems. A brief review of the algorithm proposed in [15] is presented in Section IV, while the new identification procedure is described in Section V. A simulated example is reported in Section VI in order to highlight the improvement of the presented procedure in the evaluation of the uncertainty intervals with respect to the algorithm proposed in [15].

## II. PROBLEM FORMULATION

Consider the SISO discrete-time LPV model described in terms of the linear difference equation

$$\mathcal{A}(q^{-1}, \lambda_t)w_t = \mathcal{B}(q^{-1}, \lambda_t)u_t, \quad (1)$$

where  $u_t$  and  $w_t$  are the input and the output signals respectively, while  $\lambda_t \in \mathbb{R}^\mu$ ,  $\lambda_t = [\lambda_{1,t} \lambda_{2,t} \dots \lambda_{\mu,t}]^\top$  is a vector of time-varying parameters which, according to the LPV modeling and control literature (see, e.g., [17]) are assumed to be measurable.  $\mathcal{A}(\cdot)$  and  $\mathcal{B}(\cdot)$  are polynomials in the backward shift operator  $q^{-1}$ ,

$$\mathcal{A}(q^{-1}, \lambda_t) = 1 + a_1(\lambda_t)q^{-1} + \dots + a_{na}(\lambda_t)q^{-na}, \quad (2)$$

$$\mathcal{B}(q^{-1}, \lambda_t) = b_0(\lambda_t) + b_1(\lambda_t)q^{-1} + \dots + b_{nb}(\lambda_t)q^{-nb} \quad (3)$$

where  $na \geq nb$  and the coefficients  $a_i$  and  $b_j$  are assumed to be nonlinear memoryless mappings of parameters  $\lambda_t$  described by

$$a_i(\lambda_t) = \sum_{k=1}^{n_i} a_{i,k} \phi_{i,k}(\lambda_t), \quad (4)$$

$$b_j(\lambda_t) = \sum_{h=0}^{m_j} b_{j,h} \psi_{j,h}(\lambda_t), \quad (5)$$

where  $\phi_{i,k}(\cdot)$  and  $\psi_{j,h}(\cdot)$  are known nonlinear basis functions. In our work we assume that  $\phi_{i,k}(\cdot)$  and  $\psi_{j,h}(\cdot)$  belong to the canonical polynomial basis in the parameters  $\lambda_t$ , and we denote as  $d_{\phi_{i,k}}$  and  $d_{\psi_{j,h}}$  the degree of  $\phi_{i,k}(\cdot)$  and  $\psi_{j,h}(\cdot)$ , respectively. Let  $y_t$  and  $z_t$  be the noise-corrupted measurements of  $w_t$  and  $\lambda_t$  respectively

$$y_t = w_t + \eta_t, \quad (6)$$

$$z_t = \lambda_t + \varepsilon_t, \quad (7)$$

where  $\varepsilon_t = [\varepsilon_{1,t} \varepsilon_{2,t} \dots \varepsilon_{\mu,t}]^\top$ . Measurements uncertainties  $\eta_t$  and  $\varepsilon_{s_t}$  are known to range within given bounds  $\Delta\eta_t$  and  $\Delta\varepsilon_{s_t}$ , more precisely

$$|\eta_t| \leq \Delta\eta_t, \quad (8)$$

and

$$\varepsilon_t \in \mathcal{E} = \{\varepsilon_t \in \mathbb{R}^\mu : |\varepsilon_{s_t}| \leq \Delta\varepsilon_{s_t}, s = 1, 2, \dots, \mu\} \quad (9)$$

The unknown parameter vector  $\theta \in \mathbb{R}^{n_\theta}$  to be estimated is defined as

$$\theta^\top = [a_{1,1} \dots a_{1,n_1} \dots a_{na,1} \dots a_{na,n_{na}} \quad b_{0,0} \dots b_{0,m_1} \dots b_{nb,1} \dots b_{nb,m_{nb}}], \quad (10)$$

where  $n_\theta = \sum_{i=1}^{na} n_i + \sum_{j=0}^{nb} m_j$ . In this paper we address the problem of deriving uncertainty intervals on the parameters  $\theta$ . For the sake of simplicity and without loss of generality, in the rest of the paper we only consider the case of a scalar scheduling variable  $\lambda_t$ , that is  $\lambda_t \in \mathbb{R}$ .

## III. EVALUATION OF TIGHT PARAMETERS BOUNDS

The set  $\mathcal{D}$  of all the LPV system parameters  $\theta$  and the noise samples  $\xi_t$  and  $\eta_t$  consistent with the measurement data sequence, the assumed model structure and the error bounds is described by equations (1) - (9), i.e.

$$\mathcal{D} = \left\{ (\theta, \eta, \varepsilon) \in \mathbb{R}^{n_\theta + N + (N - na)} : \begin{aligned} &\mathcal{A}(q^{-1}, z_t - \varepsilon_t)[y_t - \eta_t] = \mathcal{B}(q^{-1}, z_t - \varepsilon_t)u_t, \\ &|\varepsilon_t| \leq \Delta\varepsilon_t, \quad |\eta_r| \leq \Delta\eta_r, \\ &t = na + 1, \dots, N; \quad r = 1, \dots, N \end{aligned} \right\}. \quad (11)$$

with  $\eta = [\eta_1, \dots, \eta_N]^\top$  and  $\varepsilon = [\varepsilon_{na+1}, \dots, \varepsilon_N]^\top$ . Therefore, for  $j = 1, \dots, n_\theta$ , tight bounds on the parameter  $\theta_j$  can be computed by solving the optimization problems

$$\underline{\theta}_j = \min_{(\theta, \eta, \varepsilon) \in \mathcal{D}} \theta_j, \quad \bar{\theta}_j = \max_{(\theta, \eta, \varepsilon) \in \mathcal{D}} \theta_j. \quad (12)$$

Parameter uncertainty intervals on  $\theta_j$  are defined as  $PUI_j = [\underline{\theta}_j; \bar{\theta}_j]$ . Because of the polynomial constraints  $\mathcal{A}(q^{-1}, z_t - \varepsilon_t)[y_t - \eta_t] = \mathcal{B}(q^{-1}, z_t - \varepsilon_t)u_t$  defining the feasible region  $\mathcal{D}$ , problems (12) are nonconvex. Therefore, standard nonlinear optimization tools (gradient method, Newton method, etc.) can not be used because they can trap in local minima/maxima. As a consequence, the  $PUI_j$  obtained using these tools is not guaranteed to contain the true unknown parameter  $\theta_j$ , which is a key requirement of any set-membership identification method. One possible solution to overcome such a problem is to relax the identification problems (12) to convex optimization problems in order to numerically compute lower bounds of  $\underline{\theta}_j$  as well as upper bounds of  $\bar{\theta}_j$ . It can be shown (see [18]) that (12) are semialgebraic optimization problems with an inherent structured sparsity. Then, approximate solutions of  $\underline{\theta}_j$  and  $\bar{\theta}_j$  can be computed through a direct implementation of the *sparse* LMI relaxation techniques described in [19] and [20]. Unfortunately, due to high memory usage, the relaxation order  $\delta$  has to be rather low to implement such an identification procedure in a commercial workstation. Roughly speaking,  $\delta$  should be not greater than 2 when the number of parameters  $\theta$  is about 6 and the number  $N$  of measurements is about 30. In order to deal with problems with a larger number of measurements and parameters, a relaxation method, called static

LPV relaxation, for evaluating parameter bounds of LPV systems in the set-membership context is proposed in [15] and it is briefly reviewed in Section IV for self-consistency of the paper. In this work we propose an alternative method, called partial-dynamic LPV relaxation, which reduces the computational complexity of identification problems (12), so that the *sparse* LMI relaxation techniques described in [19] and [20] can be used to compute guaranteed parameter bounds. Such a method provides parameter bounds tighter than the ones obtained in [15].

#### IV. STATIC LPV RELAXATION

To the authors best knowledge, only one algorithm is available in the literature to evaluate parameter bounds for LPV systems when both the measurements on the output and on the time-varying parameters are affected by bounded noise. Such a method, called static LPV relaxation, was proposed in [15] where an outer-approximation  $\mathcal{D}^s$  of the feasible set  $\mathcal{D}$  has been constructed. In particular, the set  $\mathcal{D}^s$  is defined by piecewise linear constraints and, although generally nonconvex, it is the union of at most  $2^{n_\theta}$  polytopes in the parameters space  $\mathbb{R}^{n_\theta}$ . Relaxed parameter bounds  $\underline{\theta}_j^s$  and  $\bar{\theta}_j^s$  are computed by solving the optimization problems

$$\underline{\theta}_j^s = \min_{\theta \in \mathcal{D}_\theta^s} \theta_j, \quad \bar{\theta}_j^s = \max_{\theta \in \mathcal{D}_\theta^s} \theta_j. \quad (13)$$

The relaxed parameter uncertainty interval  $PUI_j^s$ , defined as  $PUI_j^s = [\underline{\theta}_j^s, \bar{\theta}_j^s]$ , is guaranteed to contain the true unknown parameter  $\theta_j$ , that is  $\theta_j \in PUI_j^s$ , for every  $j = 1, \dots, n_\theta$ .

#### V. PARTIAL-DYNAMIC LPV RELAXATION

In this section we present a new technique to relax (12) to convex optimization problems. For the sake of clarity, a general overview of the proposed method is first presented in Section V-A. Then, detailed technical results are provided in Section V-B.

##### A. Overview of the relaxation procedure

Let us rewrite  $\mathcal{D}$ , defined by (11), in the matrix form

$$\mathcal{D} = \left\{ (\theta, \eta, \varepsilon) \in \mathbb{R}^{n_\theta + 2N - na} : \begin{aligned} A [\theta^T \mathbf{1}]^T &= 0, \quad |\varepsilon_t| \leq \Delta \varepsilon_t, \quad |\eta_r| \leq \Delta \eta_r, \\ t &= na + 1, \dots, N; \quad r = 1, \dots, N \end{aligned} \right\}. \quad (14)$$

where  $A \in \mathbb{R}^{N-na, n_\theta+1}$  and the  $t$ -th row  $A_t$  of  $A$  is

$$\begin{aligned} A_t &= [(y_{t+na} - \eta_{t+na})\phi_{1,1}(z_{t+na+1} - \varepsilon_{t+na+1}), \dots, \\ & (y_t - \eta_t)\phi_{na, n_{na}}(z_{t+na+1} - \varepsilon_{t+na+1}), \\ & u_{t+na+1}\psi_{0,0}(z_{t+na+1} - \varepsilon_{t+na+1}), \dots, \\ & u_{t+na-nb}\psi_{nb, m_{nb}}(z_{t+na+1} - \varepsilon_{t+na+1}), \\ & -y_{t+na+1} + \eta_{t+na+1}]. \end{aligned} \quad (15)$$

Note that the rows of the matrix  $A$  are correlated with each other since the noise variables  $\eta_t$  appears in all the rows

$A_i$ , with  $i = t - na, t - na + 1, \dots, t$ . Besides, also the columns of the matrix  $A$  are not independent of each other, since they are correlated by the noise variable affecting the scheduling parameter. The main idea of the partial-dynamic LPV relaxation can be summarized in the following steps:

- (i) First, consider the rows of the matrix  $A$  independent with each other, keeping the correlation between the columns. This leads to the construction of an outer-bound  $\mathcal{D}^r$  of the original feasible set  $\mathcal{D}$ .
- (ii) Then, consider the columns of the matrix  $A$  independent with each other, keeping the correlation between the rows. This leads to the construction of another outer-bound  $\mathcal{D}^c$  of  $\mathcal{D}$ .
- (iii) Define the relaxed feasible parameter set  $\mathcal{D}^{rc} = \mathcal{D}^r \cap \mathcal{D}^c$  and, for every  $j = 1, \dots, n_\theta$ , compute minimum and maximum value of the parameters  $\theta_j$  over the feasible set  $\mathcal{D}^{rc}$ .

##### B. Technical results

###### Result 1: Construction of the set $\mathcal{D}^r$

Let us define the set  $\mathcal{D}^r$  as

$$\mathcal{D}^r = \left\{ (\theta, \eta, \varepsilon) \in \mathbb{R}^{n_\theta + 2N - na} : \begin{aligned} \bar{A}_t^r \theta &\geq y_t - \Delta \eta_t, \quad \underline{A}_t^r \theta \leq y_t + \Delta \eta_t, \\ |\varepsilon_t| &\leq \Delta \varepsilon_t, \quad t = na + 1, \dots, N \end{aligned} \right\}, \quad (16)$$

where  $\bar{A}_t^r$  and  $\underline{A}_t^r$  are

$$\begin{aligned} \bar{A}_t^r &= [(-y_{t-1} + \Delta \eta_{t-1} \text{sgn}(\phi_{1,1}(z_t - \varepsilon_t)) \text{sgn}(a_{1,1}))\phi_{1,1}, \dots, \\ & (-y_{t-na} + \Delta \eta_t \text{sgn}(\phi_{na, n_{na}}(z_t - \varepsilon_t)) \text{sgn}(a_{na, n_{na}}))\phi_{na, n_{na}}, \\ & u_t \psi_{0,0}(z_t - \varepsilon_t), \dots, u_{t-nb} \psi_{nb, m_{nb}}(z_t - \varepsilon_t)]. \end{aligned} \quad (17)$$

and

$$\begin{aligned} \underline{A}_t^r &= [(-y_{t-1} - \Delta \eta_{t-1} \text{sgn}(\phi_{1,1}(z_t - \varepsilon_t)) \text{sgn}(a_{1,1}))\phi_{1,1}, \dots, \\ & (-y_{t-na} - \Delta \eta_t \text{sgn}(\phi_{na, n_{na}}(z_t - \varepsilon_t)) \text{sgn}(a_{na, n_{na}}))\phi_{na, n_{na}}, \\ & u_t \psi_{0,0}(z_t - \varepsilon_t), \dots, u_{t-nb} \psi_{nb, m_{nb}}(z_t - \varepsilon_t)]. \end{aligned} \quad (18)$$

The set  $\mathcal{D}^r$  is an outer approximation of  $\mathcal{D}$ . ■

**Remark 1:** It can be proven that if the noise samples  $\eta_t$  appearing in the rows of the matrix  $A$  defined in (17) are not correlated, then  $\mathcal{D} = \mathcal{D}^r$ .

In order to construct the outer-approximation  $\mathcal{D}^c$  of  $\mathcal{D}$  we first provide the following definitions:

$$\underline{\phi}_{i,k}^t = \min_{|\varepsilon_t| \leq \Delta \varepsilon_t} \phi_{i,k}^t(z_t - \varepsilon_t), \quad \bar{\phi}_{i,k}^t = \max_{|\varepsilon_t| \leq \Delta \varepsilon_t} \phi_{i,k}^t(z_t - \varepsilon_t), \quad (19)$$

$$\underline{\gamma}_{j,h}^t = \min_{|\varepsilon_t| \leq \Delta \varepsilon_t} \gamma_{j,h}^t, \quad \bar{\gamma}_{j,h}^t = \max_{|\varepsilon_t| \leq \Delta \varepsilon_t} \gamma_{j,h}^t, \quad (20)$$

and

$$c(\phi_{i,k}^t) = \frac{\bar{\phi}_{i,k}^t + \underline{\phi}_{i,k}^t}{2}, \quad \Delta \phi_{i,k}^t = \frac{\bar{\phi}_{i,k}^t - \underline{\phi}_{i,k}^t}{2}, \quad (21)$$

$$c(\gamma_{j,h}^t) = \frac{\bar{\gamma}_{j,h}^t + \underline{\gamma}_{j,h}^t}{2}, \quad \Delta \gamma_{j,h}^t = \frac{\bar{\gamma}_{j,h}^t - \underline{\gamma}_{j,h}^t}{2} \quad (22)$$

**Result 2: Construction of the set  $\mathcal{D}^c$**

Let us define the set  $\mathcal{D}^c$  as

$$\mathcal{D}^c = \left\{ (\theta, \eta, \varepsilon) \in \mathbb{R}^{n_\theta + 2N - na} : \right. \\ \left. (A_t^c + \Delta A_t^c)\theta \geq y_t - \eta_t, (A_t^c - \Delta A_t^c)\theta \leq y_t - \eta_t, \right. \\ \left. |\eta_t| \leq \Delta \eta_t, t = na + 1, \dots, N, \right\}, \quad (23)$$

where

$$A_t^c = [-(y_{t-1} - \eta_{t-1})c(\phi_{1,1}^t), \dots, -(y_{t-na} - \eta_{t-na})c(\phi_{na,na}^t), \\ c(\gamma_{0,0}^t), \dots, c(\gamma_{nb,m_{nb}}^t)], \quad (24)$$

$$\Delta A_t^c = [(y_{t-1} - \eta_{t-1})\Delta \phi_{1,1}^t \text{sgn}(y_{t-1} - \eta_{t-1}) \text{sgn}(a_{1,1}), \dots \\ (y_{t-na} - \eta_{t-na})\Delta \phi_{na,na}^t \text{sgn}(y_{t-na} - \eta_{t-na}) \text{sgn}(a_{na,na}), \\ \Delta \gamma_{0,0}^t \text{sgn}(b_{0,0}), \dots, \Delta \gamma_{nb,m_{nb}}^t \text{sgn}(b_{nb,m_{nb}})], \quad (25)$$

Then, the set  $\mathcal{D}^c$  is an outer approximation of  $\mathcal{D}$ . ■

Proofs of Results 1 and 2 can be found in [18].

**Remark 2:** It can be proven that if the noise samples  $\lambda_t$  appearing in the elements of the row  $A_t$  in (15) are not correlated, then  $\mathcal{D} = \mathcal{D}^c$ .

**Remark 3:** Since  $\phi_{i,k}^t(\cdot)$  and  $\psi_{j,h}^t(\cdot)$  are continuous functions, the Weierstrass theorem guarantees that  $\phi_{i,k}^t(\cdot)$  and  $\gamma_{j,h}^t(\cdot)$  achieve their global minimum and maximum on the closed interval  $|\varepsilon_t| \leq \Delta \varepsilon_t$ . As is well known, such a global minimum and maximum must either be stationary points or lie on the boundary of the interval  $|\varepsilon_t| \leq \Delta \varepsilon_t$  and their computation is straightforward as  $\phi_{i,k}^t(\cdot)$  and  $\psi_{j,h}^t(\cdot)$  are polynomial functions.

An outer-approximation of  $\mathcal{D}$  tighter than both  $\mathcal{D}^r$  and  $\mathcal{D}^c$  can be defined as the intersection of  $\mathcal{D}^r$  and  $\mathcal{D}^c$ , i.e.  $\mathcal{D}^{rc} = \mathcal{D}^r \cap \mathcal{D}^c$ . Then, bounds on the parameters  $\theta_j$  can be computed by solving the optimization problems

$$\underline{\theta}_j^{pd} = \min_{(\theta, \eta, \varepsilon) \in \mathcal{D}^{rc}} \theta_j, \quad \bar{\theta}_j^{pd} = \max_{(\theta, \eta, \varepsilon) \in \mathcal{D}^{rc}} \theta_j, \quad (26)$$

and parameter uncertainty intervals on  $\theta_j$  obtained through the partial-dynamic LPV relaxation are then defined as  $PUI_j^{pd} = [\underline{\theta}_j^{pd}; \bar{\theta}_j^{pd}]$ .

**Property 1: Accuracy improvement of  $PUI_j^{pd}$  over  $PUI_j^s$**

For every  $j = 1, \dots, n_\theta$ , the parameter uncertainty interval  $PUI_j^{pd}$  is tighter than the interval  $PUI_j^s$  (obtained through the static LPV relaxation [15]), i.e.  $PUI_j^{pd} \subseteq PUI_j^s$ . ■

Proof of Property 1 is based on the fact the set  $\mathcal{D}^s$  is an outer approximation of both  $\mathcal{D}^r$  and  $\mathcal{D}^c$ . Technical details can be found in [18].

By exploiting the particular structure of the set  $\mathcal{D}^{rc}$ , we now show as parameter bounds  $\underline{\theta}_j^{pd}$  and  $\bar{\theta}_j^{pd}$  can be computed

through the solution of a set of semialgebraic optimization problems.

**Property 2: Topological features of the feasible set  $\mathcal{D}^{rc}$**

If the relative measurement error on the output  $w_t$  and on the scheduling variable  $\lambda_t$  is smaller than 100%, then the set  $\mathcal{D}^{rc}$  is the union of at most  $2^{n_\theta}$  sets  $\mathcal{D}_i^{rc}$  in  $\mathbb{R}^{n_\theta + 2N - na}$ , i.e.

$$\mathcal{D}^{rc} = \bigcup_{i=1}^{2^{n_\theta}} \mathcal{D}_i^{rc}. \quad (27)$$

The set  $\mathcal{D}_i^{rc}$  is the intersection of  $\mathcal{D}^{rc}$  with the  $i$ -th orthant  $\mathcal{O}_i$  of the parameters space  $\mathbb{R}^{n_\theta}$ , i.e.

$$\mathcal{D}_i^{rc} = \mathcal{D}^{rc} \cap \mathcal{O}_i, \quad (28)$$

The orthant  $\mathcal{O}_i$  is formally described as

$$\mathcal{O}_i = \{\theta \in \mathbb{R}^{n_\theta} : \alpha_{ij}\theta_j \geq 0, j = 1, \dots, n_\theta\}, \quad (29)$$

where  $\alpha_i \in \Gamma$ , being  $\Gamma$  the set of all  $n_\theta$ -dimensional vectors with components equal to  $\pm 1$ .

Each set  $\mathcal{D}_i^{rc}$ , if not empty, is a semialgebraic region in  $\mathbb{R}^{n_\theta + 2N - na}$  defined by polynomial inequalities of maximum degree  $d_\theta^{rc} = \max\{1 + \max_{i,k}\{d_{\phi_{i,k}}\}, 1 + \max_{j,h}\{d_{\psi_{j,h}}\}, 2\}$ . ■

Proof of Property 2 follows since in the orthant  $\mathcal{O}_i$  the sign of the parameters  $\theta$ , appearing in the definition of both  $\mathcal{D}_i^r$  and  $\mathcal{D}_i^c$ , is known. Besides, when the relative measurement error on both the output  $w_t$  and on the scheduling variable  $\lambda_t$  is smaller than 100%, also the sign of  $y_t - \eta_t$  and  $z_t - \varepsilon_t$ , appearing the definition of  $\mathcal{D}^c$  and  $\mathcal{D}^r$  respectively, is known. See [18] for technical details.

**Remark 4:** The assumption, reasonable in practice, that the relative error on the measurements of  $w_t$  and  $\lambda_t$  is smaller than 100% implies that the sign of  $y_t - \eta_t$  and  $z_t - \varepsilon_t$  is known. If such an assumption is not satisfied, then the set  $\mathcal{D}^{rc}$  is the union of at most  $2^{n_\theta + 2N - na}$  semialgebraic sets.

Thanks to Property 2, identification problems (26) can be decomposed into a collection of polynomial optimization problems. In fact, solving (26) is equivalent to compute

$$\underline{\theta}_j^{pd} = \min_{l=1, \dots, 2^{n_\theta}} \underline{\theta}_{ji}^{pd}; \quad \bar{\theta}_j^{pd} = \max_{l=1, \dots, 2^{n_\theta}} \bar{\theta}_{ji}^{pd}, \quad (30)$$

where  $\underline{\theta}_j^{pd}$  and  $\bar{\theta}_j^{pd}$  are the solutions to the following the semialgebraic optimization problems:

$$\underline{\theta}_{ji}^{pd} = \min_{(\theta, \eta, \varepsilon) \in \mathcal{D}_i^{rc}} \theta_j; \quad \bar{\theta}_{ji}^{pd} = \max_{(\theta, \eta, \varepsilon) \in \mathcal{D}_i^{rc}} \theta_j. \quad (31)$$

The inherent structured sparsity of problems (31), which will be highlighted by Property 3, is exploited to formulate sparse LMI-relaxed problems for (31) in order to compute lower (respectively upper) bounds of  $\underline{\theta}_j^{pd}$  (respectively  $\bar{\theta}_j^{pd}$ ).

By rewriting the feasible region  $\mathcal{D}_i^{rc}$  defined by (28) as

$$\mathcal{D}_i^{rc} = \left\{ (\theta, \eta, \varepsilon) \in \mathbb{R}^{n_\theta + 2N - n_a} : \right. \\
\begin{aligned}
g_t(\theta, \eta, \varepsilon) &= \bar{A}_t^r \theta - y_t + \Delta \eta_t \geq 0, \\
g_{t+N}(\theta, \eta, \varepsilon) &= -\underline{A}_t^r \theta + y_t + \Delta \eta_t \geq 0, \\
g_{t+2N}(\theta, \eta, \varepsilon) &= (A_t^c + \Delta A_t^c) \theta - y_t + \eta_t \geq 0, \\
g_{t+3N}(\theta, \eta, \varepsilon) &= -(A_t^c - \Delta A_t^c) \theta + y_t - \eta_t \geq 0, \\
g_{t+4N}(\theta, \eta, \varepsilon) &= \Delta \varepsilon_t - \varepsilon_t \geq 0, \\
g_{t+5N}(\theta, \eta, \varepsilon) &= \Delta \varepsilon_t + \varepsilon_t \geq 0, \\
g_{r+6N}(\theta, \eta, \varepsilon) &= \Delta \eta_r - \eta_r \geq 0, \\
g_{r+7N}(\theta, \eta, \varepsilon) &= \Delta \eta_r + \eta_r \geq 0, \\
g_{j+8N}(\theta, \eta, \varepsilon) &= \alpha_{ij} \theta_j \geq 0, \quad \alpha_i \in \Gamma \\
t &= na + 1, \dots, N; \quad r = 1, \dots, N; \quad j = 1, \dots, n_\theta \left. \right\}, \quad (32)
\end{aligned}$$

the inherent structured sparsity of problems (31) can be easily detected as described by the following property.

**Property 3:** Problems (31) enjoy the following features:

**P 3.1:** The functional involves only the variable  $\theta_j$ .

**P 3.2:** For every  $t = na + 1, \dots, N$ , constraints  $g_t \geq 0$  and  $g_{t+N} \geq 0$ , defining  $\mathcal{D}_i^{rc}$  in (32), depend only on the parameters  $\theta$  and the noise sample  $\varepsilon_t$ .

**P 3.3:** For every  $t = na + 1, \dots, N$ , constraints  $g_{t+2N} \geq 0$  and  $g_{t+3N} \geq 0$  depend only on the parameters  $\theta$  and the noise samples  $\eta_{t-i}$  (for  $i = 0, 1, \dots, na$ ).

**P 3.4:** For every  $t = na + 1, \dots, N$ , constraints  $g_{t+4N} \geq 0$  and  $g_{t+5N} \geq 0$  depend only on the noise variable  $\varepsilon_t$ .

**P 3.5:** For every  $r = 1, \dots, N$ , constraints  $g_{r+6N} \geq 0$  and  $g_{r+7N} \geq 0$  depend only on the noise variable  $\eta_r$ .

**P 3.6:** For every  $j = 1, \dots, n_\theta$ , the constraint  $g_{j+8N} \geq 0$  depends only on the variable  $\theta_j$ . ■

Thanks to the structured sparsity of problems (31) highlighted by Property 3, the SDP relaxation proposed in [19] and [20] can be applied to problems (31), leading to approximate solutions  $\underline{\theta}_{ji}^{pd,\delta}$  and  $\bar{\theta}_{ji}^{pd,\delta}$  that are computed by solving the convex SDP problems

$$\underline{\theta}_{ji}^{pd,\delta} = \min_{p \in \mathcal{D}_i^{pd,\delta}} f_j(p), \quad \bar{\theta}_{ji}^{pd,\delta} = \max_{p \in \mathcal{D}_i^{pd,\delta}} f_j(p), \quad (33)$$

where  $\delta$  is a given relaxation order,  $p$  is the decision variable vector, the objective function  $f_j(p)$  is linear in the variables  $p$  and the feasible region  $\mathcal{D}_i^{pd,\delta}$  is a convex set defined by linear matrix inequalities (LMIs), which takes into account the polynomial constraints defining the semialgebraic set  $\mathcal{D}_i^{rc}$  of problems (31). In particular, the number of optimization variables  $p$  is  $O(N(n_\theta + na)^{2\delta})$ , while the size of the LMI describing  $\mathcal{D}_i^{pd,\delta}$  is  $O(N(n_\theta + na)^\delta)$ . See [18] for technical details on the computation of the number of optimization variables  $p$  and of the dimension of the LMI describing the feasible region  $\mathcal{D}_i^{pd,\delta}$ .

The minimum value  $\underline{\delta}$  of the LMI relaxation order, so that (33) are well-defined, is  $\lceil \frac{\rho(\mathcal{D}_i^{rc})}{2} \rceil$ , where  $\lceil \cdot \rceil$  is the ceiling operator and  $\rho(\mathcal{D}_i^{pd,\delta})$  denotes the maximum order of the polynomial constraints defining  $\mathcal{D}_i^{rc}$ . From Property 2 the

maximum degree of the polynomial constraints describing  $\mathcal{D}_i^{pd,\delta}$  is equal to  $d_\theta^{rc}$ , therefore  $\underline{\delta} = \lceil \frac{d_\theta^{rc}}{2} \rceil$ . The reader is referred to [19] for details on the relaxation of sparse polynomial optimization problems through LMI-based relaxation techniques.

For a given relaxation order  $\delta \geq \underline{\delta}$ , let us define the  $\delta$ -relaxed uncertainty intervals obtained through the partial-dynamic-LPV procedure as  $PU I_j^{pd,\delta} = [\underline{\theta}_j^{pd,\delta}; \bar{\theta}_j^{pd,\delta}]$ , where

$$\underline{\theta}_j^{pd,\delta} = \min_{i=1,\dots,2^{n_\theta}} \underline{\theta}_{ji}^{pd,\delta}, \quad \bar{\theta}_j^{pd,\delta} = \max_{i=1,\dots,2^{n_\theta}} \bar{\theta}_{ji}^{pd,\delta}. \quad (34)$$

**Property 4:** For every  $j = 1, \dots, n_\theta$ , the  $\delta$ -relaxed parameter uncertainty interval  $PU I_j^{pd,\delta}$  satisfies the following properties.

**P 4.1: Guaranteed relaxed uncertainty intervals.**

For any relaxation order  $\delta \geq \underline{\delta}$ , the  $\delta$ -relaxed parameter uncertainty interval  $PU I_j^{pd,\delta}$  is guaranteed to contain the true unknown parameter  $\theta_j$  to be estimated, i.e.  $\theta_j \in PU I_j^{pd,\delta}$ .

**P 4.2: Monotone convergence to intervals  $PU I_j^{pd}$ .**

The  $\delta$ -relaxed parameter uncertainty interval  $PU I_j^{pd,\delta}$  becomes tighter as the relaxation order  $\delta$  increases, that is

$$PU I_j^{pd,\delta+1} \subseteq PU I_j^{pd,\delta}. \quad (35)$$

Further, as the LMI relaxation order goes to infinity, the  $\delta$ -relaxed parameter uncertainty interval  $PU I_j^{pd,\delta}$  converges to the interval  $PU I_j^{pd}$ . ■

The proof of Properties P4.1 and P4.2 (see [18] for details) follows from properties of monotone converge of sparse LMI-relaxation techniques.

## VI. SIMULATED EXAMPLE

In this section we propose a simulated example in order to show the effectiveness of the presented identification procedure and the accuracy improvement on the parameter bounds evaluation with respect to the static LPV relaxation. The considered LPV system is described by (1) with  $\mathcal{A}(q^{-1}, \lambda_t) = 1 + 0.7\lambda_t q^{-1} + (-0.4 + 0.3\lambda_t^2)q^{-2}$  and  $\mathcal{B}(q^{-1}, \lambda_t) = 0.1q^{-1} + (1.1\lambda_t + 0.3\lambda_t^2)q^{-2}$ . Therefore, the true parameters vector is  $\theta = [a_{1,1}, a_{2,1}, a_{2,2}, b_{1,1}, b_{2,1}, b_{2,2}]^T = [0.7, -0.4, 0.3, 0.1, 1.1, 0.3]^T$  and the functions  $\phi_{i,k}$  and  $\psi_{j,h}$  in (4) and (5), which depend on the scheduling parameter  $\lambda_t$ , are  $\phi_{1,1} = \lambda_t$ ,  $\phi_{2,1} = 1$ ,  $\phi_{2,2} = \lambda_t^2$ ,  $\psi_{1,1} = 1$ ,  $\psi_{2,1} = \lambda_t$  and  $\psi_{2,2} = \lambda_t^2$ . The input sequence  $\{u_t\}$  is a random uniform distributed signal which takes values in the interval  $[-1, 1]$ , while  $\lambda_t = 2 \sin(0.1t)$ . The output  $w_t$  and the scheduling signal  $\lambda_t$  are corrupted by random additive noises  $\eta_t$  and  $\varepsilon_t$ , respectively, uniformly distributed in  $[-\Delta \eta_t, +\Delta \eta_t]$  and  $[-\Delta \varepsilon_t, +\Delta \varepsilon_t]$ . The chosen error bounds  $\Delta \eta_t$  and  $\Delta \varepsilon_t$  are such that the signal to noise ratios on the output  $SNR_w$  and on the scheduling signal

$$SNR_\lambda, \text{ defined as } SNR_w = 10 \log \left\{ \frac{\sum_{t=1}^N w_t^2}{\sum_{t=1}^N \eta_t^2} \right\} \\
\text{and } SNR_\lambda = 10 \log \left\{ \frac{\sum_{t=1}^N \lambda_t^2}{\sum_{t=1}^N \varepsilon_t^2} \right\}, \text{ are equal to } 27$$

Table I: Parameter central estimates ( $\theta_j^{cs}$ ), parameter bounds ( $\underline{\theta}_j^s, \bar{\theta}_j^s$ ) and parameter uncertainties  $\Delta\theta_j^s$  obtained through the static LPV relaxation

Parameter	True Value	$\underline{\theta}_j^s$	$\theta_j^{cs}$	$\bar{\theta}_j^s$	$\Delta\theta_j^s$
$a_{1,1}$	0.700	0.546	0.729	0.913	0.1837
$a_{2,1}$	-0.400	-0.472	-0.409	-0.347	0.0627
$a_{2,2}$	0.300	0.196	0.325	0.454	0.1293
$b_{1,1}$	0.100	0.074	0.101	0.128	0.0269
$b_{2,1}$	1.100	0.923	1.129	1.335	0.2060
$b_{2,2}$	0.300	0.148	0.326	0.505	0.1785

Table II: Parameter central estimates ( $\theta_j^{cpd,\delta}$ ), parameter bounds ( $\underline{\theta}_j^{pd,\delta}, \bar{\theta}_j^{pd,\delta}$ ) and parameter uncertainties  $\Delta\theta_j^{pd,\delta}$  obtained through the partial dynamic LPV relaxation for a relaxation order  $\delta = 2$

Parameter	True Value	$\underline{\theta}_j^{pd,\delta}$	$\theta_j^{cpd,\delta}$	$\bar{\theta}_j^{pd,\delta}$	$\Delta\theta_j^{pd,\delta}$
$a_{1,1}$	0.700	0.601	0.718	0.835	0.1169
$a_{2,1}$	-0.400	-0.444	-0.409	-0.373	0.0358
$a_{2,2}$	0.300	0.193	0.282	0.372	0.0894
$b_{1,1}$	0.100	0.087	0.101	0.114	0.0132
$b_{2,1}$	1.100	0.997	1.113	1.229	0.1161
$b_{2,2}$	0.300	0.169	0.297	0.424	0.1280

db and 26 db, respectively. The number of measurements  $N$  used to compute the parameter bounds is equal to 200. First, bounds on the parameters are evaluated through the static LPV approach. The obtained relaxed bounds  $\underline{\theta}_j^s, \bar{\theta}_j^s$ , the central estimate  $\theta_j^{cs}$  and the parameter uncertainty bounds  $\Delta\theta_j^s$ , defined as  $\theta_j^{cs} = \frac{\bar{\theta}_j^s + \underline{\theta}_j^s}{2}$  and  $\Delta\theta_j^s = \frac{\bar{\theta}_j^s - \underline{\theta}_j^s}{2}$ , are reported in Table I. Then, parameters bounds are evaluated through the partial-dynamic LPV relaxation with a relaxation order  $\delta = 2$ . The Matlab package SparsePOP [21] has been exploited to relax the semialgebraic problems (31) into the SDP problems (33). In Table II the obtained parameters bounds  $\underline{\theta}_j^{pd,\delta}$  and  $\bar{\theta}_j^{pd,\delta}$  are reported, together with the central estimate  $\theta_j^{cpd,\delta}$  and the parameter uncertainty bounds  $\Delta\theta_j^{pd,\delta}$  defined as  $\theta_j^{cpd,\delta} = \frac{\bar{\theta}_j^{pd,\delta} + \underline{\theta}_j^{pd,\delta}}{2}$  and  $\Delta\theta_j^{pd,\delta} = \frac{\bar{\theta}_j^{pd,\delta} - \underline{\theta}_j^{pd,\delta}}{2}$ . Results in Tables I and II show that the true parameters are included in the parameter uncertainty intervals, as expected. Besides, the partial-dynamic LPV relaxation provides parameter bounds tighter than the ones obtained through the method proposed in [15]. As a matter of fact, even if a low value of the relaxation order  $\delta$  is used, for each parameter  $\theta_j$ , the uncertainty bound  $\Delta\theta_j^{pd,\delta}$  is at least 25% smaller than  $\Delta\theta_j^s$ .

## VII. CONCLUSION

A new technique for the evaluation of parameter uncertainty intervals for LPV systems when both the output and the scheduling signal measurements are affected by bounded noise is presented. Parameter bounds evaluation is formulated in terms of nonconvex optimization problems. In order to reduce the computational complexity of the formulated problems, the feasible set is approximated by a union of semialgebraic regions described by polynomial inequalities that involve only a small number of decision variables. Thanks to the structured sparsity of the identification problem, relaxation techniques based on linear matrix

inequalities are exploited to compute parameters uncertainty intervals, which are guaranteed to contain the true parameters. The capability of the proposed identification technique to provide a less conservative estimate of parameters bounds with respect to the previously published results is shown both theoretically and by means of a numerical example.

## REFERENCES

- [1] M. Nemani, R. Ravikanth, and B. A. Bamieh, "Identification of linear parametrically varying systems," in *Proceedings of 34th Conference on Decision and Control*, 1995, pp. 2990–2995.
- [2] L. H. Lee and K. Poolla, "Identification of linear parameter-varying systems using nonlinear programming," *ASME Journal of Dynamic Systems, Measurement and Control*, vol. 121, pp. 71–78, 1999.
- [3] B. A. Bamieh and L. Giarré, "Identification of linear parameter-varying models," *International Journal of Robust Nonlinear Control*, vol. 12, no. 9, pp. 841–853, 2002.
- [4] V. Verdult and M. Verhaegen, "Subspace identification of multivariable linear parameter-varying systems," *Automatica*, vol. 38, pp. 805–814, 2002.
- [5] —, "Kernel methods for subspace identification of multivariable LPV and bilinear systems," *Automatica*, vol. 41, pp. 1557–1565, 2005.
- [6] F. Felici, J. W. V. Wingerden, and M. Verhaegen, "Subspace identification of MIMO LPV systems using a periodic scheduling sequence," *Automatica*, vol. 43, pp. 1684–1697, 2007.
- [7] P. Lopes dos Santos, J. A. Ramos, and J. L. Martins de Carvalho, "Subspace identification of linear parameter-varying systems with innovation-type noise models driven by general inputs and a measurable white noise time-varying parameter vector," *Int. J. of Systems Science*, vol. 39, no. 9, pp. 897–911, 2008.
- [8] V. Verdult, M. Lovera, and M. Verhaegen, "Identification of linear parameter-varying state-space models with application to helicopter rotor dynamics," *International Journal of Control*, vol. 77, no. 13, pp. 1149–1159, 2004.
- [9] F. Previdi and M. Lovera, "Identification of non-linear parametrically varying models using separable least squares," *International Journal of Control*, vol. 77, no. 16, pp. 1382–1392, 2004.
- [10] R. Toth, P. S. C. Heuberger, and P. V. den Hof, "Asymptotically optimal orthonormal basis functions for LPV system identification," *Automatica*, vol. 45, no. 6, pp. 1359–1370, 2010.
- [11] R. Toth, *Modeling and identification of linear parameter-varying systems*. Springer, 2010.
- [12] M. Milanese, J. Norton, H. Piet-Lahanier, and E. Walter, Eds., *Bounding approaches to system identification*. New York: Plenum Press, 1996.
- [13] M. Sznaier and C. Mazzarzo, "An LMI approach to control-oriented identification and model (in)validation of LPV systems," *IEEE Transactions on Automatic Control*, vol. 48, no. 9, pp. 1619–1624, 2003.
- [14] G. Belforte and P. Gay, "Optimal worst case estimation for LPV-FIR models with bounded errors," *Systems & Control letters*, vol. 53, pp. 259–268, 2004.
- [15] V. Cerone and D. Regruto, "Set-membership identification of LPV models with uncertain measurements of the time-varying parameter," in *Proc. of the 47th IEEE Conference on Decision and Control*, 2008, pp. 4491–4496.
- [16] V. Cerone, D. Piga, and D. Regruto, "Set-membership LPV model identification of vehicle lateral dynamics," *Automatica*, in press.
- [17] W. J. Rugh and J. S. Shamma, "Research on gain scheduling," *Automatica*, vol. 36, no. 10, pp. 1401–1425, 2000.
- [18] V. Cerone, D. Piga, and D. Regruto, "Convex relaxation techniques for set-membership identification of LPV systems," *Internal Report*, vol. DAUIN, no. 2010/09/23, 2010.
- [19] J. Lasserre, "Convergent semidefinite relaxations in polynomial optimization with sparsity," *SIAM Journal on Optimization*, vol. 17, no. 1, pp. 822–843, 2006.
- [20] H. Waki, S. Kim, M. Kojima, and M. Muramatsu, "Sums of squares and semidefinite programming relaxations for polynomial optimization problems with structured sparsity," *SIAM Journal on Optimization*, vol. 17, no. 1, pp. 218–242, 2006.
- [21] H. Waki, S. Kim, M. Kojima, M. Muramatsu, and H. Sugimoto, "SparsePOP: a sparse semidefinite programming relaxation of polynomial optimization problems," *ACM Transaction on Mathematical Software*, vol. 35, no. 2, 2008.